Specifications

备注(Remark)
1.材料(MATERIAL)
胶芯: PA6T+30%G.F UL94V-0, 颜色:兰色.
Housing:PA6T/+30%G.F UL94V-0,Color:Blue
端子: 磷/青铜, 镍底30u"MIN,表面镀金1u"MIN
Contact:Phosphor bronze,1u"MIN GOLD PLATING OVER ALL
30u" MIN NICKEL UNDERPLATING OVER ALL
2.特性(characteristics):
额定电流: 3 AMP
Raring Current:3 AMP.
接触阻抗: 20 mΩ MAX.
Contact Resistance:20 mΩ MAX.
绝缘阻抗: 1000 MΩ MIN.
Insulating Resistance:1000 MΩ MIN.
耐电压: AC 500V.
Withstanding Voltage:AC 500V.
温度范围: -40°C to+105°C
Temperture Range: -40°C to+105°C



Ordering Information

F185-22 03 A1 B SY C 2

NO.OF PINS PER ROW	Contact Plating Full Of Gold	Contact Plating Semi-gold	INSULATOR MATERIAL:	PACKING
2~40P	A0=0.8u"	B0=0.8U"	A:PBT	A:PE Bag
	A1=1u"	B1=1U"	B:PA6T	B:Tape & Ree
	A2=1.5u"	B2=1.5U"	C:PA9T	C:Tube
	A3=2u"	B3=2U"	D:LCP	D:Tube+CAP
	A4=3u"	B4=3U"		E:Tray
	A5=5u"	B5=5U"		
	A6=10u"	B6=10U"		
	A7=15u"	B7=15U"		
	A8=20u"	B8=20U"		
	A9=30u"	B9=30U"		

S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

yxcon







REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE

OPERATION	
X.X	±0.25
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL

SCALE	Fit				
UNIT	MM				
SIZE	A4	DESIGN	丘康乐	PART NO.	F185-2203A1BSYC2
SHEET	1/1	CHECK		TITLE:	2.54mm 双排母 塑高8.5 加1.5 2*3P 180度 Y型 PC104
PROJ.		APPROVE		Customer No.	

东莞市宇熙精密连接器有限公司
Dongguan Yuxi Electronic Co.,Ltd.